



2020 SDS For: SOLACOAT MARINE COATING:

NON-HAZARDOUS ACCORDING TO NOHSC CRITERIA

***1. Identification of the substance/ preparation and the company**

Solacoat Marine Acrylic

Product Line:

Product Code:

Application:

Brushing, rolling, spraying grade of soft gloss architectural water based acrylic coating range for the painting of metal in marine site exposures.

Supplier: Coolshield International Pty Ltd ABN 12 102 333 577
 Address: P.O. Box 882, Ocean Grove Vic 3226 Australia
 Contact: Telephone: +61 (3) 5255 2063 A/H: Mob.+61 4173 41114
 Fax: +61 (3) 5256 3029 Email: info@solacoat.com.au

2. Hazards identification

Health Hazard Classification

This product is classified as non-hazardous under NOHSC criteria.

Hazard Category

Not applicable.

Risk Phrases

R36/37/38 Irritating to eyes, respiratory system and skin.
 R65 Harmful: May cause lung damage if swallowed.

Safety Phrases

S2 Keep out of the reach of children.
 S3/7/9 keep container tightly closed in a cool, well ventilated place.
 S24/25 Avoid contact with skin and eyes.

Dangerous Goods Classification

Not applicable.

Poisons Schedule

Not applicable.

3. Composition: Information on Ingredients

| Ingredient | CAS No. | Proportion % v/v |
|--------------------------------------|----------------|-------------------------|
| Acrylic co-polymer emulsion | Not regulated | 30 - ≤ 60 |
| Pigments – non-hazardous | Various | 0 - ≤ 30 |
| Propylene glycol | 57-55-6 | 10 - ≤ 30 |
| Preservative – non formaldehyde type | | 1 - ≤ 10 |
| Additives | Various | < 5 |
| Water | 7732-18-5 | Remainder |



SOLACOAT www.solacoat.com.au
TAKES THE HEAT OUT OF THE ENVIRONMENT

5. Fire Fighting Measures

Shut off product that may 'fuel' a fire if safe to do so. Allow trained personnel to attend a fire in progress, providing fire-fighters with this Material Safety Data Sheet. Prevent extinguishing media from escaping to drains and waterways. NOTE: This product is not flammable unless strongly heated in an existing fire.

Suitable extinguishing media

Water.

Hazardous products from combustion

Carbon dioxide and carbon monoxide.

Precautions for fire fighters and special protective equipment

Full protective clothing and self-contained breathing apparatus.

Hazchem Code

None.

6. Accidental Release Measures

Emergency Procedures


Prevent fluid from escaping to drains and waterways. Contain leaking packaging in a containment drum or dam constructed of inert material eg sand or other approved material. Prevent vapours from building up in confined areas. Ensure that drain valves are closed at all times. Clean up and report spills immediately.

Methods and materials for containment

Major Land Spill

- Prevent liquid from entering sewers, watercourses or low-lying areas.
- Keep the public away from the area.
- Advise authorities if substance has entered a watercourse or sewer or has contaminated soil or vegetation.

(to be continued)



2020 SDS SOLACOAT MARINE COATING:

6. Accidental Release Measures (continued)

- Take measures to minimise the effect on ground water.
- Contain the spilled liquid with sand or earth.
- Recover by pumping – use pump or hand pump – or with a suitable absorbent material.
- Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.
- See “First Aid Measure” and “Stability and Reactivity” sections.

Major Water Spill

- Notify the port or relevant authority and keep the public away from the area.
- Shut off the source of the spill if possible and safe to do so.
- Confine the spill if possible.
- Remove the product from the surface by skimming or with suitable absorbent material.
- Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.
- See “First Aid Measure” and “Stability and Reactivity” sections.

7. Handling and Storage

Precautions for safe handling

This product is non -flammable. Keep container closed. Handle containers with care. Open slowly to control possible pressure release.

Conditions for safe storage

Store in a cool, dry place away from direct sunlight. Keep out of the reach of children.

Incompatible materials

Acids, Oxidising Agents or Chemicals.

8. Exposure Controls: Personal Protection

National Exposure Standards

The time weighted average concentration (TWA) for this product is: None specified - which means the highest allowable exposure concentration in an eight-hour day for a five-day working week. The short-term exposure limit (STEL) is: None specified, which is the maximum allowable exposure concentration at any time.

Biological limit values

None established.

Engineering Controls: Ventilation

The use of local exhaust ventilation is recommended to control process emissions near the source. Laboratory samples should be handled in a fume hood. Provide mechanical ventilation of confined spaces. Use explosion-proof ventilation equipment.

Personal Protective Equipment

Respiratory Protection

Where concentrations in air may exceed the limits described in the National Exposure Standards, it is Recommended to use a half-face filter mask to protect from overexposure by inhalation. A type ‘A’ filter material is considered suitable for this product. It is recommended that a suitable dust mask and eye protection are worn when sanding the dried film of paint coating.


Eye protection

Always use safety glasses or a face shield when handling this product.

Skin/ Body Protection

Always wear long sleeves and long trousers or coveralls, and enclosed footwear or safety boots when handling this product. It is recommended that chemical resistant gloves be worn when using this product.

(to be continued)



2020SDS SOLACOAT MARINE COATING:

8. Exposure controls/ Personal protection (continued)

Protection and hygienic measures

Keep away from foodstuffs, drinks and tobacco. Wash hands before breaks and at the end of work. Keep working clothes separate. Take off immediately any contaminated clothing.

Flammability

Product is non-flammable. However, it will burn when strongly heated in an existing fire.

9. Physical and chemical properties

| Property | Unit of measurement | Typical value |
|------------------------------|---------------------|-----------------|
| Appearance | - | Coloured liquid |
| Boiling Point/ Range | °C | 100 (Water) |
| Flash point | °C | Non-flammable |
| Density @ 25°C | g/ ml | 1.00 – 1.30 |
| Vapour Pressure @ 20°C | kPa | Water |
| Explosive Limits (LEL – UEL) | % | Not applicable |
| Vapour Density @ 20°C | kPa | Not available |
| Auto-ignition Temperature | °C | Not applicable |
| Viscosity @ 25°C | Seconds | Not applicable |
| Percent volatiles | % | 40 – 60 |
| Solubility in water | % w/w | Miscible |

Remarks:

The values for density and viscosity are guide values.

10. Stability and reactivity

Chemical stability

Stable under normal conditions of use.

Conditions to avoid

Sources of heat and ignition, open flames.

Hazardous decomposition products

No hazardous decomposition products when stored and handled correctly except on burning. See "Fire Fighting Measures".

11. Toxicological information

Health Effects:


Acute:

Swallowed: May cause irritation to the throat, mouth and digestive tract. Large doses may cause drowsiness and may lead to unconsciousness. Aspiration of liquid into lungs may cause serious (even fatal) pneumonitis.

Eye: Irritant, both by contact and vapour.

Skin: Irritant, both by contact and vapour. Prolonged exposure may result in dryness and cracking.

(to be continued)



2020SDS SOLACOAT MARINE COATING:

11. Toxicological Information (continued)

Inhaled: Vapour is irritating to mucous membranes and respiratory tract. Can cause dizziness, headaches, nausea and may lead to unconsciousness. Prolonged exposure to vapour may cause damage to the central nervous system.

Chronic: Principal routes of exposure are usually by skin contact with the material and inhalation of vapour/ spray mist. Prolonged or repeated skin contact may cause drying and/or cracking with irritation and possible dermatitis following. As with any chemical product, contact with unprotected bare skin; inhalation of vapours, mist or dust in a work place environment; or ingestion in any form should be avoided by observing good occupational work practices.

Advice to Doctor: Treat symptomatically.

12. Ecological information **Aquatic Toxicity**

Fish Toxicity (rainbow trout, goldfish, and bluegill)

LC₅₀ (96 hr): Based on data for similar components or preparations, this product is expected to be toxic to aquatic organisms.

Daphnia Magna EC₅₀ (48 hr):

Long term adverse effects to aquatic organisms are possible if continuous exposure is maintained.

Remark:

On the basis of the data for ecotoxicological effects, the substance can be classified as non-critical to aquatic organisms in the water-soluble range. As the substance is not readily biodegradable, long retention times in water are to be expected. This applies only in cases where no other elimination mechanisms (photodegradation, hydrolysis, adsorption) are active. However, as there is no ecotoxic effect, no damage to the ecosystem is to be expected.

Do not allow to escape into waterways, waste water or soil.

13. Disposal considerations

The relevant local, regional and national regulations must be complied with. It is among the tasks of the polluter to assign the waste to waste codes specific to industrial sectors and processes according to the national authority. It is recommended that details be worked out with the waste disposal company responsible.

The waste can be disposed of in a suitable incinerator or approved landfill site, provided that national/ local legislation is complied with.

For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.

After final product withdrawal, all residues must be removed from containers (drip-free, powder-free or paste-free). Once the product residues adhering to the walls of the containers have been rendered harmless, the product and hazard labels must be invalidated. Containers must be recycled in compliance with national and environmental regulations.



2020 SDS SOLACOAT MARINE COATING:

*14. Transport information

| | | | | | |
|--|-----------------------------|----------|------|------|--|
| Non-hazardous Good according to ADG Code (7 th Edition) | | Hazchem: | | None | |
| GGVSE: 3 | UN No: None | PG: None | SP: | | |
| RID/ ADR: 3 | UN No: None | PG: None | SP: | | |
| Warning sign: | Hazard No. None UN No. 1263 | | | | |
| ADNR: 3 | UN No: None | PG: None | SP: | | |
| GGVSee/ IMDG: 3 | UN No: None | PG: None | MPO: | | |
| ICAO-TI/ IATA-DGR: 3 | UN No: None | PG: None | | | |
| Declaration for land shipment: | PAINT | | | | |
| Declaration for sea shipment: | PAINT | | | | |
| Declaration for shipment by air: | PAINT | | | | |

Limited quantity regulations applicable in accordance with chapter 3.4 RID/ ADR in compliance with threshold value.
Other information:
Keep dry. Keep separated from foodstuffs.

15. Regulatory Information

Not a scheduled poison under SUSDP.
Labelling as required by Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 (CHIP3), in accordance with Australian requirements.
Symbol: Xi, Hazard description: Irritant

R22 Harmful if swallowed.
R36/37/38 Irritating to eyes, respiratory system and skin.
R65 Harmful: May cause lung damage if swallowed.
R66 Repeated exposure may cause skin dryness and cracking.
R67 Vapours may cause drowsiness and dizziness.
S2 Keep out the reach of children.
S3/7/9 Keep container tightly closed in a cool, well ventilated place.
S24/25 Avoid contact with skin and eyes.
S51 Use only in well ventilated areas.
S62 If swallowed, and more than 15 minutes from hospital or a medical centre induce vomiting: seek medical advice immediately and show this container or label.

*16. Other information

All components of this product are listed in the European Inventory of Existing Commercial Substances (EINECS) under the provisions laid down in the corresponding EC-Directive. The components are also listed in the Australia Inventory of Chemical Substances (NICNAS).

Text of all R-phrases referred to in Sections 2 and 3:

| | |
|---------------|--|
| R 20: | Harmful by inhalation. |
| R 20/ 21: | Harmful by inhalation and in contact with skin. |
| R 23: | Toxic by inhalation. |
| R 36: | Irritating to the eyes. |
| R 38: | Irritating to the skin. |
| R 36/ 37/ 38: | Irritating to the eyes, respiratory system and skin. |

This Safety Data Sheet replaces all previous information.
Revised and valid from: Date of Issue: 14-4-2020

The data given here is based on current knowledge and experience. The purpose of this Material Safety Data Sheet is to describe the products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance.

End of Report.